



General Specifications



Cabinets with a 2-prefix that are 24" to 36" wide are full-access with no vertical frame members, and full-width drawers.

- **Face Frames:** All Showplace cabinetry face frames are made of 3/4" thick select solid hardwood components. Stiles and rails are joined together with concealed screws and wood glue for strength. Frames are dadoed to receive tops, bottoms, and end panels.

- **End Panels:** Cabinet end panels are 3/8" plywood. Exposed ends that are called-out on the order will receive wood veneer which is stained, sealed, and top coated. Interior is covered with light birch printed melamine. End panels are dadoed to receive tops, bottoms, and backs.

- **Tops and Bottoms:** Cabinet tops and bottoms are 3/8" plywood laminated with light birch melamine on both sides (a few selected base corner cabinet exceptions are noted in their respective section information).

- **Backs:** Cabinet backs are 1/8" thick plywood laminated with matching light birch melamine on the interior.

- **Backrails:** Cabinet backrails are 5/8" thick plywood. Backrails are hidden from view on the inside of cabinets.

- **Shelving:** Standard interior shelving is 3/4" particleboard laminated on two sides with light birch melamine and matching PVC edgebanding on one long edge. Finished interior cabinets will receive 3/4" veneer surfaced shelving with matching wood specie edgebanding on one long edge.

- **Toeboards:** Cabinet toe kicks are 5/8" plywood which fits between end panels and

reaches the cabinet bottom. Toeboard trim is suggested to finish installation (TM0240).

- **Drawers:** Showplace cabinetry utilizes a four-sided drawer constructed with 3/4" hardwood, using dovetailed joinery. Bottoms are 1/4" plywood, fully captive within sides and ends.

- **Drawer Slides:** The standard drawer slide is a 7/8-extension ball-bearing undermount glide. A soft-closing Blumotion full-extension ball-bearing undermount upgrade is available. Both types of glides are rated for 75-pound dynamic loads (working load with weight equally distributed, independently tested for thousands of cycles), and 100-pound static loads (weight at front edge of half-open drawer, independently tested for short period).

- **Finish:** Showplace cabinetry features hand-applied finish which is sealed and given an oven-baked topcoat of catalyzed varnish for lasting durability.